# SPARTA 600 LED

# astro

#### GENERAL

LOCATION: Bathroom
CLASS: CETLus (Class 1)

LOCATION RATING: Damp
DRIVER REQUIRED: Mains 120V

INSTALLATION ORIENTATION: Wall Mount - Horizontal & Vertical FITTING METHOD: 4" Octagon Box with Canopy Kit

MAIN MATERIAL:

DIMENSIONS (mm):

DIMENSIONS (inch):

CUT OUT HOLE (mm/inch):

Metal - Aluminium

H: 600 W: 33 D: 80

H: 23.62 W: 1.3 D: 3.15

CUT OUT HOLE (mm/inch):

RECESS DEPTH (mm/inch):

FIRE RATING:

CABLE LENGTH (mm/inch):

GROSS WEIGHT (lb):

ADA COMPLIANT:

Yes

IC RATING:

# LAMP

LIGHT SOURCE: Mid-Power LED

WATTAGE: 7.2W

LAMP INCLUDED: Yes (Integral)

MAXIMUM LAMP LENGTH (mm/inch):

LUMINOUS FLUX (lm):

COLOUR TEMP (K):

3000

CRI (Ra):

MACADAM ELLIPSE:

TILT ADJUSTABLE ANGLE (°):

ROTATION ADJUSTABLE ANGLE (°):

LIFETIME (hrs):

54000

BEAM ANGLE (°):

-

## **ELECTRICAL**

SWITCHED: No
DIMMABLE: Yes
DIMMING METHOD: 0-10V
SUPPLY FREQUENCY (Hz): 50/60
DRIVER/BALLAST VOLTAGE (V): 100-277
DRIVER LIFETIME (hrs): 63500
EFFICACY (Im/W): 99

### ADDITIONAL INFORMATION:

SHADE INCLUDED: -

SHADE/DIFFUSER MATERIAL: Plastic
SHADE/DIFFUSER FINISH White
F MARK: -



CODE: 1322009 (8378) FINISH: POLISHED CHROME

TO MAINTAIN THIS PRODUCT TO ITS BEST CONDITION, PLEASE VIEW OUR CARE AND CLEANING GUIDELINES ON THE SUPPORT SECTION OF THE ASTRO WEBSITE.

ASTRO® IS A REGISTERED TRADEMARK OF ASTRO LIGHTING LIMITED. ASTRO LIGHTING'S FIXTURE DESIGNS AND IMAGERY ARE PROTECTED UNDER U.S. AND INTERNATIONAL INTELLECTUAL PROPERTY LAWS, AND ALL RIGHTS TO SUCH DESIGNS AND IMAGERY ARE EXPRESSLY RESERVED.

Please note that some dimensions may vary slightly due to manufacturing tolerances, this includes cable entry and fixing holes.



