ASCOLITWIN

GENERAL

LOCATION: Interior

CLASS: cETLus (Class 1)

Dry LOCATION RATING:

DRIVER REQUIRED: Mains 120V

INSTALLATION ORIENTATION: Ceiling & Wall Mount FITTING METHOD: 4" Octagon Box MAIN MATERIAL: Metal - Aluminium DIMENSIONS (mm): H: 130 W: 350 D: 110 DIMENSIONS (inch): H: 5.12 W: 13.78 D: 4.33

CUT OUT HOLE (mm/inch): RECESS DEPTH (mm/inch): FIRE RATING: CABLE LENGTH (mm/inch): GROSS WEIGHT (Ib):

4.18

ADA COMPLIANT: Yes - if installed in compliance

with ADA 307.4 IC RATING:

LAMP

LIGHT SOURCE: GU10 WATTAGE: 2 X 50W LAMP INCLUDED: Nο MAXIMUM LAMP LENGTH (mm/inch): 57

LUMINOUS FLUX (Im): Lamp Dependent COLOUR TEMP (K): Lamp Dependent CRI (Ra): Lamp Dependent MACADAM ELLIPSE: Lamp Dependent

TILT ADJUSTABLE ANGLE (°): 90 ROTATION ADJUSTABLE ANGLE (°):

LIFETIME (hrs): Lamp Dependent BEAM ANGLE (°): Lamp Dependent

ELECTRICAL

SWITCHED: No DIMMABLE: Yes

DIMMING METHOD: Lamp Dependent

SUPPLY FREQUENCY (Hz): DRIVER/BALLAST VOLTAGE (V): DRIVER LIFETIME (hrs):

EFFICACY (Im/W): Lamp Dependent


ADDITIONAL INFORMATION:

SHADE INCLUDED:

SHADE/DIFFUSER MATERIAL: Metal SHADE/DIFFUSER FINISH Matt Nickel

F MARK: Suitable for mounting on flammable materials







CODE: 1286073 FINISH: BRONZE



CODE: 1286074 FINISH: MATT NICKEL

TO MAINTAIN THIS PRODUCT TO ITS BEST CONDITION, PLEASE VIEW OUR CARE AND CLEANING GUIDELINES ON THE SUPPORT SECTION OF THE ASTRO WEBSITE.

ASTRO® IS A REGISTERED TRADEMARK OF ASTRO LIGHTING LIMITED. ASTRO LIGHTING'S FIXTURE DESIGNS AND IMAGERY ARE PROTECTED UNDER U.S. AND INTERNATIONAL INTELLECTUAL PROPERTY LAWS, and all rights to such designs and imagery are expressly RESERVED.

Please note that some dimensions may vary slightly due to manufacturing tolerances, this includes cable entry and fixing holes.

