## GENERAL

LOCATION: Bathroom
CLASS: CETLus (Class 1)

LOCATION RATING:

Damp

DRIVER REQUIRED:

Mains 120V

INSTALLATION ORIENTATION:

FITTING METHOD:

MAIN MATERIAL:

DIMENSIONS (mm):

DIMENSIONS (inch):

Damp

Mains 120V

Ceiling Mount

4" Octagon Box

Metal - Mild Steel

H: 225 W: 225 D: 165

DIMENSIONS (inch):

H: 8.86 W: 8.86 D: 6.5

CUT OUT HOLE (mm/inch):

RECESS DEPTH (mm/inch):

FIRE RATING:

CABLE LENGTH (mm/inch):

GROSS WEIGHT (lb):

3.78

ADA COMPLIANT: Yes - if installed in compliance

with ADA 307.4

IC RATING:

## LAMP

LIGHT SOURCE: E26/Medium
WATTAGE: 60W
LAMP INCLUDED: No

RECOMMENDED LAMP: 12W Max LED E26/Medium

MAXIMUM LAMP LENGTH (mm/inch): -

LUMINOUS FLUX (Im):Lamp DependentCOLOUR TEMP (K):Lamp DependentCRI (Ra):Lamp DependentMACADAM ELLIPSE:Lamp Dependent

TILT ADJUSTABLE ANGLE (°): ROTATION ADJUSTABLE ANGLE (°): -

LIFETIME (hrs): Lamp Dependent
BEAM ANGLE (°): Lamp Dependent

## **ELECTRICAL**

SWITCHED: No DIMMABLE: Yes

DIMMING METHOD: Lamp Dependent

SUPPLY FREQUENCY (Hz): DRIVER/BALLAST VOLTAGE (V): DRIVER LIFETIME (hrs): -

EFFICACY (Im/W): Lamp Dependent

## ADDITIONAL INFORMATION:

SHADE INCLUDED: SHADE/DIFFUSER MATERIAL: SHADE/DIFFUSER FINISH -

F MARK: Suitable for mounting

on flammable materials



CODE: 1291002

FINISH: POLISHED CHROME

TO MAINTAIN THIS PRODUCT TO ITS BEST CONDITION, PLEASE VIEW OUR CARE AND CLEANING GUIDELINES ON THE SUPPORT SECTION OF THE ASTRO WEBSITE.

ASTRO® IS A REGISTERED TRADEMARK OF ASTRO LIGHTING LIMITED. ASTRO LIGHTING'S FIXTURE DESIGNS AND IMAGERY ARE PROTECTED UNDER U.S. AND INTERNATIONAL INTELLECTUAL PROPERTY LAWS, AND ALL RIGHTS TO SUCH DESIGNS AND IMAGERY ARE EXPRESSLY RESERVED.

Please note that some dimensions may vary slightly due to manufacturing tolerances, this includes cable entry and fixing holes.



