# ZERO ROUND

#### GENERAL

LOCATION: Interior

CLASS: cETLus (Class 1)

LOCATION RATING: Damp DRIVER REQUIRED: Mains 120V INSTALLATION ORIENTATION: Ceiling Mount FITTING METHOD: 4" Octagon Box MAIN MATERIAL: Metal - Mild Steel DIMENSIONS (mm): D: 50 Ø: 450 DIMENSIONS (inch): D:1.97 Ø:17.72

CUT OUT HOLE (mm/inch): RECESS DEPTH (mm/inch): FIRE RATING: CABLE LENGTH (mm/inch): GROSS WEIGHT (Ib): 8.58

ADA COMPLIANT: Yes - if installed in compliance

with ADA 307.4

IC RATING:

### LAMP

LIGHT SOURCE: Mid-Power LED

WATTAGE: 16.5W

LAMP INCLUDED: Yes (Integral)

MAXIMUM LAMP LENGTH (mm/inch): LUMINOUS FLUX (Im): 1252 COLOUR TEMP (K): 3000 90 CRI (Ra): MACADAM ELLIPSE: 3-Step TILT ADJUSTABLE ANGLE (°): ROTATION ADJUSTABLE ANGLE (°): LIFETIME (hrs): 54000

**ELECTRICAL** 

BEAM ANGLE (°):

SWITCHED: No DIMMABLE: Yes DIMMING METHOD: 0-10V SUPPLY FREQUENCY (Hz): 47-53 DRIVER/BALLAST VOLTAGE (V): 120-277 DRIVER LIFETIME (hrs): 10900 EFFICACY (Im/W): 76

## ADDITIONAL INFORMATION

SHADE INCLUDED: SHADE MATERIAL:

F MARK: Suitable for mounting

on flammable materials



CODE: 1382004 FINISH: MATT WHITE

TO MAINTAIN THIS PRODUCT TO ITS BEST CONDITION, PLEASE VIEW OUR CARE AND CLEANING GUIDELINES ON THE SUPPORT SECTION OF THE ASTRO WEBSITE.

ASTRO® IS A REGISTERED TRADEMARK OF ASTRO LIGHTING LIMITED. ASTRO LIGHTING'S FIXTURE DESIGNS AND IMAGERY ARE PROTECTED UNDER U.S. AND INTERNATIONAL INTELLECTUAL PROPERTY LAWS, and all rights to such designs and imagery are expressly RESERVED.

Please note that some dimensions may vary slightly due to manufacturing tolerances, this includes cable entry and fixing holes.





