FUSE 3 astro

GENERAL

LOCATION: Interior

CLASS: cULus (Class 1)

LOCATION RATING: Dry

DRIVER REQUIRED: Mains 120V INSTALLATION ORIENTATION: Wall Mount

FITTING METHOD: Included Junction Box

MAIN MATERIAL: Metal

 DIMENSIONS (mm):
 H: 200 W: 75 D: 102

 DIMENSIONS (inch):
 H: 7.87 W: 2.95 D: 4.02

 CUT OUT HOLE (mm/inch):
 L: 194 W: 67.1/L: 7.64 W: 2.64

RECESS DEPTH (mm/inch): 70/2.76
FIRE RATING: -

CABLE LENGTH (mm/inch):

GROSS WEIGHT (lb):

ADA COMPLIANT:

IC RATING:

IC Rated

LAMP

LIGHT SOURCE: High Power LED

WATTAGE: 2W

LAMP INCLUDED: Yes (Integral)

17

MAXIMUM LAMP LENGTH (mm/inch): LUMINOUS FLUX (lm): 185
COLOUR TEMP (K): 2700
CRI (Ra): 90
MACADAM ELLIPSE: 3-Step
TILT ADJUSTABLE ANGLE (°): 90
ROTATION ADJUSTABLE ANGLE (°): 330
LIFETIME (hrs): 60000

ELECTRICAL

BEAM ANGLE (°):

SWITCHED: Yes

DIMMABLE: No

DIMMING METHOD:
SUPPLY FREQUENCY (Hz): 50-60

DRIVER/BALLAST VOLTAGE (V): 100-277

DRIVER LIFETIME (hrs): 30000

EFFICACY (Im/W): 57

ADDITIONAL INFORMATION:

SHADE INCLUDED: SHADE/DIFFUSER MATERIAL: SHADE/DIFFUSER FINISH -

F MARK: Suitable for mounting on flammable materials



CODE: 1215091 FINISH: MATT WHITE



CODE: 1215092 FINISH: MATT BLACK



CODE: 1215093 FINISH: POLISHED CHROME



CODE: 1215094 FINISH: MATT NICKEL



CODE: 1215095 FINISH: BRONZE



CODE: 1215102 FINISH: MATT GOLD

TO MAINTAIN THIS PRODUCT TO ITS BEST CONDITION, PLEASE VIEW OUR CARE AND CLEANING GUIDELINES ON THE SUPPORT SECTION OF THE ASTRO WEBSITE.

ASTRO® IS A REGISTERED TRADEMARK OF ASTRO LIGHTING LIMITED. ASTRO LIGHTING'S FIXTURE DESIGNS AND IMAGERY ARE PROTECTED UNDER U.S. AND INTERNATIONAL INTELLECTUAL PROPERTY LAWS, AND ALL RIGHTS TO SUCH DESIGNS AND IMAGERY ARE EXPRESSLY RESERVED.

Please note that some dimensions may vary slightly due to manufacturing tolerances, this includes cable entry and fixing holes.







