

# KOS ROUND 140 LED

astro

## GENERAL

|                           |                                                 |
|---------------------------|-------------------------------------------------|
| LOCATION:                 | Bathroom/Interior/Exterior                      |
| CLASS:                    | cULus (Class 1)                                 |
| LOCATION RATING:          | Wet                                             |
| DRIVER REQUIRED:          | Mains 120V                                      |
| INSTALLATION ORIENTATION: | Ceiling Mount                                   |
| FITTING METHOD:           | 4" Octagon Box                                  |
| MAIN MATERIAL:            | Metal - Aluminum                                |
| DIMENSIONS (mm):          | H: 142 Ø: 115                                   |
| DIMENSIONS (inch):        | H: 5.59 Ø: 4.53                                 |
| CUT OUT HOLE (mm/inch):   | -                                               |
| RECESS DEPTH (mm/inch):   | -                                               |
| FIRE RATING:              | -                                               |
| CABLE LENGTH (mm/inch):   | -                                               |
| GROSS WEIGHT (lb):        | 2.03                                            |
| ADA COMPLIANT:            | Yes - if installed in compliance with ADA 307.4 |
| IC RATING:                | -                                               |

## LAMP

|                                |                |
|--------------------------------|----------------|
| LIGHT SOURCE:                  | AC LED Module  |
| WATTAGE:                       | 11.4W          |
| LAMP INCLUDED:                 | Yes (Integral) |
| MAXIMUM LAMP LENGTH (mm/inch): | -              |
| LUMINOUS FLUX (lm):            | 721            |
| COLOUR TEMP (K):               | 2700           |
| CRI (Ra):                      | 90             |
| MACADAM ELLIPSE:               | 3-Step         |
| TILT ADJUSTABLE ANGLE (°):     | -              |
| ROTATION ADJUSTABLE ANGLE (°): | -              |
| LIFETIME (hrs):                | L70 >40000     |
| BEAM ANGLE (°):                | 36             |

## ELECTRICAL

|                             |                                 |
|-----------------------------|---------------------------------|
| SWITCHED:                   | No                              |
| DIMMABLE:                   | Yes                             |
| DIMMING METHOD:             | Phase - Leading & Trailing Edge |
| SUPPLY FREQUENCY (Hz):      | 50/60                           |
| DRIVER/BALLAST VOLTAGE (V): | 110-130                         |
| DRIVER LIFETIME (hrs):      | 40000                           |
| EFFICACY (lm/W):            | 63                              |

## ADDITIONAL INFORMATION

|                 |                                              |
|-----------------|----------------------------------------------|
| SHADE INCLUDED: | -                                            |
| SHADE MATERIAL: | -                                            |
| F MARK:         | Suitable for mounting on flammable materials |



CODE: 1326029  
FINISH: TEXTURED WHITE



CODE: 1326030  
FINISH: TEXTURED BLACK



CODE: 1326031  
FINISH: TEXTURED GREY

TO MAINTAIN THIS PRODUCT TO ITS BEST CONDITION, PLEASE VIEW OUR CARE AND CLEANING GUIDE ON THE SUPPORT SECTION OF THE ASTRO WEBSITE.

Pour entretenir au mieux ce produit, veuillez consulter notre guide d'entretien et de nettoyage, dans la rubrique d'aide sur le site Web d'Astro.

Um dieses Produkt im besten Zustand zu erhalten, beachten Sie bitte unseren Leitfaden zu Pflege und Reinigung im Abschnitt „Support“ auf der Astro-Website.

Per mantenere questo prodotto nelle sue migliori condizioni, consultare la nostra guida per la manutenzione e la pulizia nella sezione dedicata all'assistenza del sito Web Astro.

# PRODUCT ELEVATIONS

astro

Please note that some dimensions may vary slightly due to manufacturing tolerances, this includes cable entry and fixing holes.

