GENERAL

LOCATION: Interior

CLASS: cULus (Class 1)

LOCATION RATING: Dry

DRIVER REQUIRED: Mains 120V

INSTALLATION ORIENTATION: Wall Mount - Horizontal & Vertical

FITTING METHOD: Included Junction Box

MAIN MATERIAL: Metal - Zinc

DIMENSIONS (mm): H: 45 W: 200 D: 43 DIMENSIONS (inch): H: 1.77 W: 7.87 D: 1.69 CUT OUT HOLE (mm/inch): L: 165.1/6.5 W: 35.1/1.38

RECESS DEPTH (mm/inch): 55/2.17 FIRE RATING: CABLE LENGTH (mm/inch): GROSS WEIGHT (Ib): 3.65

ADA COMPLIANT: Yes - if installed in compliance with

ADA 307.2, 308, 309.3, 309.4

IC RATING: IC. Rated

LAMP

LIGHT SOURCE: High Powered LED

WATTAGE: 1W

LAMP INCLUDED: Yes (Integral)

MAXIMUM LAMP LENGTH (mm/inch): LUMINOUS FLUX (Im): 61 COLOUR TEMP (K): 2700 90 CRI (Ra): MACADAM ELLIPSE: 3-Step TILT ADJUSTABLE ANGLE (°): 135 ROTATION ADJUSTABLE ANGLE (°): 180 60000 LIFETIME (hrs): BEAM ANGLE (°): 26

ELECTRICAL

SWITCHED: Yes DIMMABLE: DIMMING METHOD: SUPPLY FREQUENCY (Hz): 50/60 DRIVER/BALLAST VOLTAGE (V): 100-240 DRIVER LIFETIME (hrs): 60000 EFFICACY (Im/W): 27

ADDITIONAL INFORMATION:

SHADE INCLUDED: SHADE/DIFFUSER MATERIAL: SHADE/DIFFUSER FINISH

F MARK: Suitable for mounting

on flammable materials



CODE: 1157004 FINISH: POLISHED CHROME



CODE: 1157005 FINISH: MATT NICKEL



CODE: 1157006 FINISH: BRONZE



CODE: 1157009 FINISH: MATT GOLD



CODE: 1157013 FINISH: BRONZE

TO MAINTAIN THIS PRODUCT TO ITS BEST CONDITION, PLEASE VIEW OUR CARE AND CLEANING GUIDELINES ON THE SUPPORT SECTION OF THE ASTRO WEBSITE.

ASTRO® IS A REGISTERED TRADEMARK OF ASTRO LIGHTING LIMITED. ASTRO LIGHTING'S FIXTURE DESIGNS AND IMAGERY ARE PROTECTED UNDER U.S. AND INTERNATIONAL INTELLECTUAL PROPERTY LAWS, and all rights to such designs and imagery are expressly RESERVED.

Please note that some dimensions may vary slightly due to manufacturing tolerances, this includes cable entry and fixing holes.







